



SIGNMAX EXIM

Once A Deal. Always A Deal.

SIGNMAX EXIM PVT. LTD. ® Technical Data Sheet

Self Adhesive Vinyl – FVG 9012/ FVM 9012

Film: Monomeric Calendar PVC Film, 100 Microns – Glossy/Matte (Pure White)

Glue Property: Semi- Removable Clear Adhesive

Liner: 120 Gsm, One Side PE and Silicon coated wood pulp paper

Width: 1.02/1.27/1.52 Meters

Product Features:

1. Strong tensile and weather resistance.
2. Film is flat.
3. Low Shrinkable rate, less water wave.
4. Premium PVC Level.
5. Excellent ink absorption property and high color ability.

Product Application:

1. Temporary promotional and point of sale advertising
2. Indoor and Outdoor advertising graphic signs.
3. Vehicle Advertising; Display
4. Eco-solvent inkjet printer, Solvent Inkjet Printer, UV and Latex Printers.
5. Paste on the surfaces which is flat, smooth clean, dust-free surface, and no peeling of the skin.

Detecting Conditions:

1. Indoor Temperature: 23°C ± 2
2. Relative Humidity (%RH): 50°C ±5
3. Storage Condition: 25°C ± 2
4. Posting Requirements: 20°C ± 10
5. Applicable Temperature: -20°C-70°C
6. Glossy Rate: 50%, Less 10% for Matte

Warranty Condition:

1. Shelf Life one year: SAV should be stored in suitable conditions, preferably used within 12 months
2. Serviceable life one year: The best printing is at a temperature of 23°C ± 2 and a relative humidity of 50°C ±5.
3. Prosecution period one year: from the product provided date, no-acceptance for overdue product.

