

SIGNMAX EXIM PVT. LTD. ® Technical Data Sheet

Self Adhesive Vinyl - FVG Grey Back/ FVM Grey Back

Film: Monomeric Calendar PVC Film, 100 Microns - Glossy/Matte

Glue Property: Semi-Removable Grey Adhesive

Liner: 120 Gsm PE-Silicon Coating Paper

Width: 1.02/1.27/1.52 Meters

Product Features:

- 1. Strong tensile and weather resistance
- 2. Film is flat.
- 3. Low Shrinkable rate, less water wave.
- 4. High Quality solvent based glue.
- 5. Excellent ink absorption property and high color ability

Product Application:

- 1. Temporary promotional and point of sale advertising
- 2. Indoor and Outdoor advertising graphic signs.
- 3. Vehicle Advertising; Display
- 4. Eco-solvent inkjet printer, Solvent Inkjet Printer, UV Inkjet Printer
- 5. Paste on the surfaces which is flat, smooth clean, dust-free surface, and no peeling of the skin.

Detecting Conditions:

- 1. Indoor Temperature: 23°C ± 2
- 2. Relative Humidity (%RH): 50±5
- 3. Storage Condition: 25°C ± 2
- 4. Posting Requirements: 20°C ± 10
- 5. Glossy Rate: 50%, Less 10% for Matte

Warranty Condition:

- 1. Shelf Life one year: SAV should be stored in suitable conditions, preferably used within 12 months
- 2. Serviceable life one year: The best printing is at a temperature of $23^{\circ}\text{C} \pm 2$ and a relative humidity of $50^{\circ}\text{C} \pm 5$.
- 3. Prosecution period one year: from the product provided date, no-acceptance for overdue product.











